

BMA FIRE RETARDANT PAINT

Code: MOR-THR

Color: Aluminium, black

PROPERTIES

BMA Fire Retardant Paint is a silicone resin-based coating. It is a two-hour fire retardant. It can be used as an interior / exterior aluminum pigmented finish. BMA Fire Retardant Paint is It has good adhesion and hiding power. It is suitable for steel and aluminum surfaces. It can be used at surfaces like hot pipelines, smoke stacks, stoves and exhaust pipes which are exposed to high heat.

RECOMMENDED USES

BMA Fire Retardant Paint can be used for:

- ✓ Chimneys and exhausts pipes
- ✓ Domestic stoves, industrial ovens
- ✓ Engine parts

PERFORMANCE BENEFITS

- ✓ 2-hour Fire Retardant
- ✓ Can be used as an interior/exterior aluminum pigmented finish
- ✓ Good impact and abrasion resistance
- ✓ Durable and hard wearing
- ✓ Air drying at ambient temperature
- ✓ Rust preventive
- ✓ Remarkable colour retention

CHARACTERISTIC PHYSICO-CHEMICAL DATA

*Data corresponding to **BMA Fire Retardant Paint**, MOR-THR*

Tests	Norms	Results
Total solids, by weight	ASTM D2369	50%
Total solids, by volume	ISO 3233	28 ± 2%
Consistency, @ 25°C	ASTM D562	2 Poises
Specific Gravity (Kg/L)	ASTM D1475	1.1 ± 0.05
Total Volatile Organic Compound (VOC)	ASTM D3960	495 g/L
Theoretical Coverage (m ² /L) (Typical film thickness)	-	14.00
Typical dry film thickness (µm)	-	20
Typical wet film thickness (µm)	-	71

APPLICATIONS GUIDE

Surface Preparation

Before applying BMA Fire Retardant Paint, all necessary pretreatment must be done. Surface should be clean, dry and free of all contaminants (oils, agents, dust, dirt, etc...) in order to avoid the risk of surface failing.

Metal surfaces

For new steel, clean the surface from any oil or grease residues using a solution (1:10) of Eksen Kimya (1 L of EKSEN KIMYA DL50 dissolved in 10 L of water). Sand the substrate to Sa 2½ until smoothing then remove all sanding dust and let it dry before any primer application.

For painted steel, remove loose and peeling paint using mechanical methods such as sanding and sandblasting of the entire surface until smoothing so the new coating can adhere properly. When the old paint is compatible with the new one, only light sanding is required. Then, remove persistent dirt and sanding residues with a detergent solution.

For non-ferrous metal (galvanized steel, aluminum, stainless steel, iron, etc...), use BMA Wash Primer BMA-WPU in order to etch the substrate, remove any corrosion residues and promote adhesion to the subsequently applied coatings. In case of unweathered surface or when weathering is not possible, apply a sweep or brush blast cleaning using a non-metallic abrasive in order to lightly roughen the surface. Let the surface dry before coating application.

Application

BMA Fire Retardant Paint should be applied in a well-ventilated area where the relative humidity does not exceed 85% and the temperature is at least 5°C.

The surface should be clean, dry and free of all contaminants before applying the BMA Fire Retardant Paint using an air spraying system or it can be applied using a brush or roller.

Drying Time

At 23°C:

Surface (touch) Dry: 40 minutes

Hard Dry: 4 hours

Dry to overcoat: 12 hours

AVAILABLE PACKAGING

Kilo – US gallon = 3.785L – Pail = 20L

SHELF LIFE

BMA Fire Retardant Paint should be stored in tightly closed and undamaged containers where the temperature varies between 5 °C and 35°C. Exposure to direct sunlight and freezing should be avoided.

Under the above-mentioned conditions, the shelf-life BMA Fire Retardant Paint will be 1 year. After this period, the paint quality is subjected to re-inspection. Proper handling is required to maintain good quality.

HEALTH & SAFETY

Before using this product, please consult our Safety Data Sheet (SDS) for complete information on Hazards Identification, First-Aid and Fire-Fighting Measures, Accidental Release Measures, Handling and Storage, Exposure Control and Personal Protection, Stability and Reactivity, Toxicological Information, and Transport Information.

QUALITY ASSURANCE

BMA Commercial & Industrial s.a.l is a holder of the ISO 9001:2015 and ISO 45001:2018 certificates, which guarantees that all operations are conducted in compliance with International Standards.

TDS.204 - Edition #: 2

IMPORTANT: The statements, technical information and recommendations contained herein are believed to be accurate. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, BMA Commercial & Industrial s.a.l expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.